## NSN 5365-01-049-9543

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-01-049-9543 **Thread Class:** 2a **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened **Overall Length:** 0.125 inches Diameter: Between 0.069 inches and 0.072 inches **Thread Size:** 1.594-32 **Bore Diameter:** 1.188 inches Depth: 0.125 inches **Bore Shape:** Straight **Screw Thread Series Designator:** N special **Drive Type:** Drilled face **Accommodation Type And Quantity:** 4 holes Angle Between Accommodations In Deg: 90.0 **Radius From Geometric Axis To Accommodation:** 0.656 inches **Beveled Thread:** Not included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** Not included **Bore Edge Process:** Any acceptable Material: Cres astm a582 type 303 condva Material: Cres astm a582 type 303 condva **Surface Treatment:** 

Passivated qq-p-35

## NSN 5365-01-049-9543

Externally Threaded Ring - Page 2 of 2



	Trea	

Passivated qq-p-35

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

T252-d