NSN 5365-01-049-9561

Nonmetallic Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5365-01-049-9561

| Nonme | tallic | Hardness | Rating: |
|---------|--------|-----------------|---------|
| MOHILLE | taille | naiulless | naumu. |

35.0 shore durometer a and 45.0 shore durometer a

Overall Length:

Between 0.330 inches and 0.350 inches

Center Hole Diameter:

Between 0.190 inches and 0.210 inches

Design Type:

Single centrally located hole

Tapered Body Largest Diameter:

Between 0.770 inches and 0.790 inches

Tapered Body Smallest Diameter:

Between 0.280 inches and 0.300 inches

Longer Taper Smallest Diameter:

Between 0.430 inches and 0.450 inches

Tapered Portion Height:

Between 0.080 inches and 0.100 inches

Bottom Tapered Portion Height:

Between 0.240 inches and 0.260 inches

Material:

Rubber chloroprene class cr

Material Specification:

Mil-r-6855, class 2, grade 40 military specification single material response

Style Designator:

Round tapered

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A535j0

Mil-std (military Standard):

Mil-r-6855 spec.