NSN 5365-01-052-1451

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-01-052-1451 **Thread Class:** 2a **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened Width: Between 0.031 inches and 0.041 inches **Overall Length:** Between 0.145 inches and 0.150 inches **Thread Size:** 0.375-24 **Bore Diameter:** Between 0.202 inches and 0.208 inches Between 0.046 inches and 0.056 inches Bore Shape: Straight **Screw Thread Series Designator:** Unf **Drive Type:** Slotted face **Thread Location:** Both ends **Accommodation Type And Quantity:** 2 slots Angle Between Accommodations In Deg: 180.0 **Beveled Thread:** Included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** Not included **Bore Edge Process:** Any acceptable Material: Cres astm a581 type 303 cond a or cres astm a581 type 303se cond a Material: Cres astm a581 type 303 cond a or cres astm a581 type 303se cond a

Passivate

Surface Treatment:

NSN 5365-01-052-1451

Externally Threaded Ring - Page 2 of 2



	Trea	

Passivated, qq-p-35

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T252-d