

View Online at <https://aerobasegroup.com/nsn/5365-01-056-1804>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Casehardening Indicator:**

Not casehardened

**Width:**

0.063 inches

**Overall Length:**

Between 0.220 inches and 0.230 inches

**Thread Size:**

0.750-32

**Bore Diameter:**

Between 0.437 inches and 0.442 inches

**Depth:**

Between 0.050 inches and 0.060 inches

**Bore Shape:**

Straight

**Screw Thread Series Designator:**

Un

**Drive Type:**

Slotted face

**Accommodation Type And Quantity:**

2 slots

**Angle Between Accommodations In Deg:**

180.0

**Beveled Thread:**

Not included

**Bore Annular Internal Serration:**

Not included

**Setscrew Locking Notch:**

Not included

**Bore Edge Process:**

Any acceptable

**Special Features:**

Surface treatment bbqq-p-35 and tc-p-636 or painted tt-p-664 and painted tt-e-529

**Material:**

Cres astm a582 type 303 cond a or cres astm a582 type 303se cond a

**Material:**

Cres astm a582 type 303 cond a or cres astm a582 type 303se cond a

**Surface Treatment:**

Passivate and paint or primer and enamel semigloss

**Surface Treatment:**

Passivated, qq-p-35 and painted tt-p-636 or painted tt-p-664 and painted tt-e-529

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T252-d