

View Online at <https://aerobasegroup.com/nsn/5365-01-056-1804>

Thread Class:

2a

Thread Direction:

Right-hand

Casehardening Indicator:

Not casehardened

Width:

0.063 inches

Overall Length:

Between 0.220 inches and 0.230 inches

Thread Size:

0.750-32

Bore Diameter:

Between 0.437 inches and 0.442 inches

Depth:

Between 0.050 inches and 0.060 inches

Bore Shape:

Straight

Screw Thread Series Designator:

Un

Drive Type:

Slotted face

Accommodation Type And Quantity:

2 slots

Angle Between Accommodations In Deg:

180.0

Beveled Thread:

Not included

Bore Annular Internal Serration:

Not included

Setscrew Locking Notch:

Not included

Bore Edge Process:

Any acceptable

Special Features:

Surface treatment bbqq-p-35 and tc-p-636 or painted tt-p-664 and painted tt-e-529

Material:

Cres astm a582 type 303 cond a or cres astm a582 type 303se cond a

Material:

Cres astm a582 type 303 cond a or cres astm a582 type 303se cond a

Surface Treatment:

Passivate and paint or primer and enamel semigloss

Surface Treatment:

Passivated, qq-p-35 and painted tt-p-636 or painted tt-p-664 and painted tt-e-529

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T252-d