Machine Thread Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5365-01-059-7944

| View Online at https://aerobasegroup.com/nsn/5365-01-059-7944         |
|---|
| Thread Direction:   |
| Right-hand  |
| Overall Length:   |
| 0.330 inches  |
| Thickness:  |
| 0.050 inches  |
| Wrenching Facility Shape:   |
| Hexagon   |
| Screw Thread Length:  |
| 0.250 inches  |
| Width Across Flats:   |
| 0.250 inches  |
| Hole Inside Diameter:   |
| Between 0.125 inches and 0.126 inches                                 |
| Thready Qty Per Inch (tpi):   |
| 28  |
| Thread Size:  |
| 12.000 inches   |
| Material:   |
| Steel comp 303  |
| Material Specification:   |
| Astm a582 assn standard single material response                      |
| Surface Treatment:  |
| Oxide   |
| Surface Treatment Specification:                                      |
| Mil-c-13924, class 4 military specification single treatment response |
| Thread Series Designator:   |
| Unf   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A540s0  |
| Mil-std (military Standard):  |
| Mil-c-13924 spec.   |
|   |