## NSN 5365-01-068-8753

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-01-068-8753 **Thread Class:** За **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened **Overall Length:** Between 0.245 inches and 0.255 inches Diameter: Between 0.120 inches and 0.130 inches **Thread Size:** 1.125-12 **Bore Diameter:** Between 0.589 inches and 0.599 inches Between 0.245 inches and 0.255 inches **Bore Shape:** Straight **Screw Thread Series Designator:** Un **Drive Type:** Drilled face **Accommodation Type And Quantity:** 2 holes Angle Between Accommodations In Deg: 180.0 **Beveled Thread:** Not included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** Included **Special Features:** Has two setscrew notches, 9o.O degrees apart and centered 30.0 degrees from the wrenching holes Material: Steel, qq-s-763, class 303 Material: Steel comp 303 **Surface Treatment: Passivate** 

· accivate

**Surface Treatment:** 

Passivated, mil-s-5002

## NSN 5365-01-068-8753

Externally Threaded Ring - Page 2 of 2



_				-		
C	h	Δ	Iŧ.		ife:	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

T252-d