

View Online at <https://aerobasegroup.com/nsn/5365-01-074-7825>

Thread Class:

3a

Thread Direction:

Right-hand

Casehardening Indicator:

Not casehardened

Overall Length:

Between 0.367 inches and 0.383 inches

Diameter:

Between 0.132 inches and 0.148 inches

Bore Diameter:

Between 1.698 inches and 1.702 inches

Depth:

Between 0.117 inches and 0.133 inches

End Application:

C-130h

Bore Shape:

Straight

Drive Type:

Drilled face

Accommodation Type And Quantity:

2 holes

Angle Between Accommodations In Deg:

180.0

Radius From Geometric Axis To Accommodation:

1.000 inches

Beveled Thread:

Not included

Bore Annular Internal Serration:

Not included

Setscrew Locking Notch:

Not included

Criticality Code Justification:

Abxv

Special Features:

Counterbore, 2.276 to 2.286 in. Dia. And 0.157 in. Deep, on face opposite wrenching side. Seven threaded holes, 0.086-56unc-2b, equally spaced on 2.062 in. Dia. Bolt circle, 0.375 in. Deep (thru).

Material:

Aluminum alloy, qq-a-225/8, alloy 6061, t6

Material:

Aluminum alloy 6061

Surface Treatment:

Anodic coating, black, 580-0024-000

Surface Treatment:

Anodic coating, black, 580-0024-000

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T252-d