

View Online at <https://aerobasegroup.com/nsn/5365-01-074-7825>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Casehardening Indicator:**

Not casehardened

**Overall Length:**

Between 0.367 inches and 0.383 inches

**Diameter:**

Between 0.132 inches and 0.148 inches

**Bore Diameter:**

Between 1.698 inches and 1.702 inches

**Depth:**

Between 0.117 inches and 0.133 inches

**End Application:**

C-130h

**Bore Shape:**

Straight

**Drive Type:**

Drilled face

**Accommodation Type And Quantity:**

2 holes

**Angle Between Accommodations In Deg:**

180.0

**Radius From Geometric Axis To Accommodation:**

1.000 inches

**Beveled Thread:**

Not included

**Bore Annular Internal Serration:**

Not included

**Setscrew Locking Notch:**

Not included

**Criticality Code Justification:**

Abxv

**Special Features:**

Counterbore, 2.276 to 2.286 in. Dia. And 0.157 in. Deep, on face opposite wrenching side. Seven threaded holes, 0.086-56unc-2b, equally spaced on 2.062 in. Dia. Bolt circle, 0.375 in. Deep (thru).

**Material:**

Aluminum alloy, qq-a-225/8, alloy 6061, t6

**Material:**

Aluminum alloy 6061

**Surface Treatment:**

Anodic coating, black, 580-0024-000

**Surface Treatment:**

Anodic coating, black, 580-0024-000

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T252-d