NSN 5365-01-080-5661

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-01-080-5661 **Thread Class:** 2a **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened Width: Between 0.125 inches and 0.145 inches **Overall Length:** Between 0.480 inches and 0.520 inches **Thread Size:** 3.000-16 **Bore Diameter:** Between 2.560 inches and 2.580 inches Between 0.100 inches and 0.140 inches **End Application:** Bomb, laser guided Bore Shape: Straight **Screw Thread Series Designator:** Unc **Drive Type:** Slotted face **Thread Location:** End opposite drive end **Accommodation Type And Quantity:** Angle Between Accommodations In Deg: 180.0 **Beveled Thread:** Not included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** Not included **Criticality Code Justification:** Feat **Special Features:** Thread length: 0.420 in. (on drive end); tolerance and fit are critical Material:

Aluminum alloy, qq-a-225/9, alloy 7075, t651

NSN 5365-01-080-5661

Externally Threaded Ring - Page 2 of 2



ate	

Aluminum alloy 7075

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T252-d