NSN 5365-01-088-7248

Plate Spacer - Page 1 of 1

Mil-std (military Standard):

Mil-a-8625 spec.



View Online at https://aerobasegroup.com/nsn/5365-01-088-7248 **Hole Diameter:** Between 0.205 inches and 0.210 inches **Bolt Circle Diameter:** 2.374 inches **Overall Width:** 2.714 inches **Aperture Diameter:** Between 1.725 inches and 1.735 inches **Outside Corner Radius:** 0.170 inches **Outside Corner Inverted Radius:** Between 0.151 inches and 0.161 inches **Side Radius From Gasket Center:** Between 2.175 inches and 2.185 inches **Bolt Hole Quantity: Special Features:** On one side the i.D. Is counterbored, 2.056 to 2.062 in. Diameter and 0.088 to 0.092 in. Deep; the other face has a sleeve extending 0.120 in. From face (dimension included in characteristic-adum) with an o.D. Of 1.765 to 1.775 in. The body-sleeve corner is rounded, 0.010 in. Radius, and the counterbore-i.D. Corner is rounded, 0.040 in. Radius Material: Aluminum alloy 7075 **Material Specification:** Qq-a-225/9, t6 federal specification single material response **Surface Treatment:** Anodize **Surface Treatment Specification:** Mil-a-8625, type 2 military specification single treatment response Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig: A07000