

View Online at <https://aerobasegroup.com/nsn/5365-01-090-1206>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Casehardening Indicator:**

Not casehardened

**Overall Length:**

Between 0.590 inches and 0.610 inches

**Diameter:**

Between 0.141 inches and 0.150 inches

**Thread Size:**

2.250-16

**Bore Diameter:**

Between 1.520 inches and 1.540 inches

**Depth:**

Between 0.270 inches and 0.330 inches

**Bore Shape:**

Straight

**Screw Thread Series Designator:**

Un

**Drive Type:**

Drilled face

**Thread Location:**

Both ends

**Accommodation Type And Quantity:**

4 holes

**Angle Between Accommodations In Deg:**

90.0

**Radius From Geometric Axis To Accommodation:**

0.910 inches

**Beveled Thread:**

Included

**Bore Annular Internal Serration:**

Not included

**Setscrew Locking Notch:**

Not included

**Special Features:**

Threaded end counterbored 1.860 in. Nom diameter by 0.345 in. Nom depth, 7 holes 0.051 in. Nom diameter perpendicular and equally spaced through drive end

**Material:**

Aluminum alloy, qq-a-225/8, alloy 6061, t6 or aluminum alloy, qq-a-225/8, alloy 6061, t651

**Material:**

Aluminum alloy 6061 or aluminum alloy 6061

**Surface Treatment:**

Anodize ems52401 type 1 cl a

**Surface Treatment:**

Anodize ems52401 type 1 cl a

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T252-d