

View Online at <https://aerobasegroup.com/nsn/5365-01-090-1206>

Thread Class:

3a

Thread Direction:

Right-hand

Casehardening Indicator:

Not casehardened

Overall Length:

Between 0.590 inches and 0.610 inches

Diameter:

Between 0.141 inches and 0.150 inches

Thread Size:

2.250-16

Bore Diameter:

Between 1.520 inches and 1.540 inches

Depth:

Between 0.270 inches and 0.330 inches

Bore Shape:

Straight

Screw Thread Series Designator:

Un

Drive Type:

Drilled face

Thread Location:

Both ends

Accommodation Type And Quantity:

4 holes

Angle Between Accommodations In Deg:

90.0

Radius From Geometric Axis To Accommodation:

0.910 inches

Beveled Thread:

Included

Bore Annular Internal Serration:

Not included

Setscrew Locking Notch:

Not included

Special Features:

Threaded end counterbored 1.860 in. Nom diameter by 0.345 in. Nom depth, 7 holes 0.051 in. Nom diameter perpendicular and equally spaced through drive end

Material:

Aluminum alloy, qq-a-225/8, alloy 6061, t6 or aluminum alloy, qq-a-225/8, alloy 6061, t651

Material:

Aluminum alloy 6061 or aluminum alloy 6061

Surface Treatment:

Anodize ems52401 type 1 cl a

Surface Treatment:

Anodize ems52401 type 1 cl a

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T252-d