NSN 5365-01-092-1239

Sleeve Spacer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5365-01-092-1239

Overall	Lenath:
Overan	LCHAHI.

Between 0.8550 inches and 0.8570 inches

Body Outside Diameter:

Between 0.9600 inches and 0.9800 inches

Body Inside Diameter:

Between 0.8500 inches and 0.8700 inches

Left Internal Flange Hole Diameter:

Between 0.7400 inches and 0.7600 inches

Left Internal Flange Width:

Between 0.1000 inches and 0.1300 inches

Left Flange Outside Diameter:

Between 1.0227 inches and 1.0232 inches

Right Flange Outside Diameter:

Between 1.0227 inches and 1.0232 inches

Left Flange Width:

Between 0.1300 inches and 0.1700 inches

Right Flange Width:

Between 0.1300 inches and 0.1700 inches

Corner Shape:

Square all corners

Special Features:

Internal flange chamfered inside corner 30 degrees also through one wall four holes 0.375 in. Dia

Material:

Aluminum alloy 6061

Material Specification:

Qq-a-225/8, t651 federal specification single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Ems 52401 type 1, cl c, fscm 99193 mfr ref single treatment response

Style Designator:

18c-1 solid, external flanges both ends, internal flange one end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A045a0