NSN 5365-01-093-1097

Optical Elements Lock Ring - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5365-01-093-1097

	_	
General	110000	'Intion:
General	DESCI	IDUIDII.

Demilitarization:

No

Dsteel, corrosion resisting, qq-s-763 comp 303; 4.156 in. Straight bore id; 3.971 in. Min and 3.981 in. Maximum tapered bore dia;	0.188 in.
Ht. outside edge threaded notches 0.062 in. W.bv.0.094 in. Deen	

Dsteel, corrosion resisting, qq-s-763 comp 303; 4.156 in. Straight bore id; 3.971 in. Min and 3.981 in. Maximum tapered bore dia; 0.971 in. Min and 3.981 in. Maximum tapered bore dia; 0.971 in. Min and 3.981 in. Maximum tapered bore dia; 0.971 in. Min and 3.981 in. Maximum tapered bore dia; 0.971 in. Min and 3.981 in. Maximum tapered bore dia; 0.971 in. Min and 3.981 in. Maximum tapered bore dia; 0.971 in. Min and 3.981 in. Maximum tapered bore dia; 0.971 in. Min and 3.981 in. Maximum tapered bore dia; 0.971 in. Min and 3.981 in. Maximum tapered bore dia; 0.971 in. Min and 3.981 in. Maximum tapered bore dia; 0.971 in. Min and 3.981 in. Maximum tapered bore dia; 0.971 in. Min and 3.981 in. Maximum tapered bore dia; 0.971 in. Min and 3.981 in. Maximum tapered bore dia; 0.971 in. Min and 3.981 in. Maximum tapered bore dia; 0.971 in. Min and 3.981 in. Maximum tapered bore dia; 0.971 in. Min and 3.981 in	0.188 in
Ht; outside edge threaded notches 0.062 in. W by 0.094 in. Deep	
Shelf Life:	
N/a	
Unit Of Measure:	