NSN 5365-01-094-0719

Sleeve Spacer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5365-01-094-0719

1.5000 inches Body Outside Diameter: 0.7500 inches Body Inside Diameter: 0.5100 inches Body Inside Diameter: 0.5100 inches Corner Shape: Square all corners Special Features: 2 bolt holes 0.250 in. Diameter drilled from outside diameter clear through to the opposite outside dia, located 0.310 in. From each e having 0.880 in. Ctr to ctr distance between bolt holes Material: Steel comp 304 or steel Material Specification: Mil-t-8504 military specification 1st material response or aisi, comp 6770 assn standard 2nd material response Style Designator: 17c solid, plain, no outside flanges Shelf Life: N/a Unit Of Measure: Demilitarization:	
0.7500 inches Body Inside Diameter: 0.5100 inches Corner Shape: Square all corners Special Features: 2 bolt holes 0.250 in. Diameter drilled from outside diameter clear through to the opposite outside dia, located 0.310 in. From each ethaving 0.880 in. Ctr to ctr distance between bolt holes Material: Steel comp 304 or steel Material Specification: Mil-t-8504 military specification 1st material response or aisi, comp 6770 assn standard 2nd material response Style Designator: 17c solid, plain, no outside flanges Shelf Life: N/a Unit Of Measure: Demilitarization:	
Body Inside Diameter: 0.5100 inches Corner Shape: Square all corners Special Features: 2 bolt holes 0.250 in. Diameter drilled from outside diameter clear through to the opposite outside dia, located 0.310 in. From each ethaving 0.880 in. Ctr to ctr distance between bolt holes Material: Steel comp 304 or steel Material Specification: Mil-t-8504 military specification 1st material response or aisi, comp 6770 assn standard 2nd material response Style Designator: 17c solid, plain, no outside flanges Shelf Life: N/a Unit Of Measure: Demilitarization:	
Corner Shape: Square all corners Special Features: 2 bolt holes 0.250 in. Diameter drilled from outside diameter clear through to the opposite outside dia, located 0.310 in. From each el having 0.880 in. Ctr to ctr distance between bolt holes Material: Steel comp 304 or steel Material Specification: Mil-t-8504 military specification 1st material response or aisi, comp 6770 assn standard 2nd material response Style Designator: 17c solid, plain, no outside flanges Shelf Life: N/a Unit Of Measure: Demilitarization:	
Corner Shape: Square all corners Special Features: 2 bolt holes 0.250 in. Diameter drilled from outside diameter clear through to the opposite outside dia, located 0.310 in. From each ethaving 0.880 in. Ctr to ctr distance between bolt holes Material: Steel comp 304 or steel Material Specification: Mil-t-8504 military specification 1st material response or aisi, comp 6770 assn standard 2nd material response Style Designator: 17c solid, plain, no outside flanges Shelf Life: N/a Unit Of Measure: Demilitarization:	
Square all corners Special Features: 2 bolt holes 0.250 in. Diameter drilled from outside diameter clear through to the opposite outside dia, located 0.310 in. From each ethaving 0.880 in. Ctr to ctr distance between bolt holes Material: Steel comp 304 or steel Material Specification: Mil-t-8504 military specification 1st material response or aisi, comp 6770 assn standard 2nd material response Style Designator: 17c solid, plain, no outside flanges Shelf Life: N/a Unit Of Measure: Demilitarization:	
Special Features: 2 bolt holes 0.250 in. Diameter drilled from outside diameter clear through to the opposite outside dia, located 0.310 in. From each enhaving 0.880 in. Ctr to ctr distance between bolt holes Material: Steel comp 304 or steel Material Specification: Mil-t-8504 military specification 1st material response or aisi, comp 6770 assn standard 2nd material response Style Designator: 17c solid, plain, no outside flanges Shelf Life: N/a Unit Of Measure: Demilitarization:	
2 bolt holes 0.250 in. Diameter drilled from outside diameter clear through to the opposite outside dia, located 0.310 in. From each en having 0.880 in. Ctr to ctr distance between bolt holes Material: Steel comp 304 or steel Material Specification: Mil-t-8504 military specification 1st material response or aisi, comp 6770 assn standard 2nd material response Style Designator: 17c solid, plain, no outside flanges Shelf Life: N/a Unit Of Measure: Demilitarization:	
having 0.880 in. Ctr to ctr distance between bolt holes Material: Steel comp 304 or steel Material Specification: Mil-t-8504 military specification 1st material response or aisi, comp 6770 assn standard 2nd material response Style Designator: 17c solid, plain, no outside flanges Shelf Life: N/a Unit Of Measure: Demilitarization:	
Material: Steel comp 304 or steel Material Specification: Mil-t-8504 military specification 1st material response or aisi, comp 6770 assn standard 2nd material response Style Designator: 17c solid, plain, no outside flanges Shelf Life: N/a Unit Of Measure: Demilitarization:	nd
Steel comp 304 or steel Material Specification: Mil-t-8504 military specification 1st material response or aisi, comp 6770 assn standard 2nd material response Style Designator: 17c solid, plain, no outside flanges Shelf Life: N/a Unit Of Measure: Demilitarization:	
Material Specification: Mil-t-8504 military specification 1st material response or aisi, comp 6770 assn standard 2nd material response Style Designator: 17c solid, plain, no outside flanges Shelf Life: N/a Unit Of Measure: Demilitarization:	
Mil-t-8504 military specification 1st material response or aisi, comp 6770 assn standard 2nd material response Style Designator: 17c solid, plain, no outside flanges Shelf Life: N/a Unit Of Measure: Demilitarization:	
Style Designator: 17c solid, plain, no outside flanges Shelf Life: N/a Unit Of Measure: Demilitarization:	
17c solid, plain, no outside flanges Shelf Life: N/a Unit Of Measure: Demilitarization:	
Shelf Life: N/a Unit Of Measure: Demilitarization:	
N/a Unit Of Measure: Demilitarization:	
Unit Of Measure: Demilitarization:	
 Demilitarization:	
ALC:	
No	
Fiig:	
A045a0	
Mil-std (military Standard):	
Mil-t-8504 spec.	