Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-01-096-7224

| Thread Pitch Diameters: |
|---|
| +3.5365/+3.5409 inches |
| Thread Direction: |
| Right-hand |
| Casehardening Indicator: |
| Not casehardened |
| Width: |
| 0.094 inches |
| Overall Length: |
| Between 0.260 inches and 0.270 inches |
| Thread Size: |
| 3.5625-32 |
| Bore Diameter: |
| 3.208 inches |
| Depth: |
| 0.090 inches |
| Bore Shape: |
| Straight |
| Screw Thread Series Designator: |
| Uns |
| Drive Type: |
| Slotted face |
| Accommodation Type And Quantity: |
| 4 slots |
| Angle Between Accommodations In Deg: |
| 90.0 |
| Beveled Thread: |
| Not included |
| Bore Annular Internal Serration: |
| Not included |
| Setscrew Locking Notch: |
| Not included |
| Material: |
| Steel, astm a582 type 303se condition a |
| Material: |
| Steel, astm a582 type 303se condition a |
| Surface Treatment: |
| Passivate |
| Surface Treatment: |
| Passivated, qq-p-35 |
| Shelf Life: |
| N/a |

NSN 5365-01-096-7224

Externally Threaded Ring - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

T252-d