

View Online at <https://aerobasegroup.com/nsn/5365-01-110-7315>

Thread Pitch Diameters:

+2.5991/+2.6034 inches

Thread Direction:

Right-hand

Casehardening Indicator:

Not casehardened

Chamfer Angle In Deg:

45.0

Chamfer Length:

0.015 mils and 0.047 centimeters

Width:

Between 0.063 inches and 0.078 inches

Overall Length:

Between 0.240 inches and 0.260 inches

End Radius:

1.313 inches

Taper Minor Diameter:

Between 1.800 inches and 1.810 inches

Taper Major Diameter:

Between 2.145 inches and 2.155 inches

Thread Size:

2.625-32

Depth:

Between 0.063 inches and 0.078 inches

Bore Shape:

Tapered

Screw Thread Series Designator:

Uns

Drive Type:

Slotted face

Accommodation Type And Quantity:

2 slots

Angle Between Accommodations In Deg:

180.0

Beveled Thread:

Not included

Taper Major Diameter Location:

Drive end

Bore Annular Internal Serration:

Not included

Setscrew Locking Notch:

Not included

Bore Edge Process:

Chamfered

Process End Location:

Both ends

Material:

Aluminum alloy, qq-a-200/3, alloy 2024, t4 or aluminum alloy, qq-a-200/8, alloy 6061, t6 or aluminum alloy, qq-a-225/6, alloy 2024, t6 or aluminum alloy, qq-a-225/6, t4 or aluminum alloy, qq-a-225/8, alloy 6061, t6

Material:

Aluminum alloy 2024 or aluminum alloy 6061 or aluminum alloy 2024 or aluminum alloy 2024 or aluminum alloy 6061

Surface Treatment:

Black dye

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T252-d