

View Online at <https://aerobasegroup.com/nsn/5365-01-110-7315>

**Thread Pitch Diameters:**

+2.5991/+2.6034 inches

**Thread Direction:**

Right-hand

**Casehardening Indicator:**

Not casehardened

**Chamfer Angle In Deg:**

45.0

**Chamfer Length:**

0.015 mils and 0.047 centimeters

**Width:**

Between 0.063 inches and 0.078 inches

**Overall Length:**

Between 0.240 inches and 0.260 inches

**End Radius:**

1.313 inches

**Taper Minor Diameter:**

Between 1.800 inches and 1.810 inches

**Taper Major Diameter:**

Between 2.145 inches and 2.155 inches

**Thread Size:**

2.625-32

**Depth:**

Between 0.063 inches and 0.078 inches

**Bore Shape:**

Tapered

**Screw Thread Series Designator:**

Uns

**Drive Type:**

Slotted face

**Accommodation Type And Quantity:**

2 slots

**Angle Between Accommodations In Deg:**

180.0

**Beveled Thread:**

Not included

**Taper Major Diameter Location:**

Drive end

**Bore Annular Internal Serration:**

Not included

**Setscrew Locking Notch:**

Not included

**Bore Edge Process:**

Chamfered

**Process End Location:**

Both ends

**Material:**

Aluminum alloy, qq-a-200/3, alloy 2024, t4 or aluminum alloy, qq-a-200/8, alloy 6061, t6 or aluminum alloy, qq-a-225/6, alloy 2024, t6 or aluminum alloy, qq-a-225/6, t4 or aluminum alloy, qq-a-225/8, alloy 6061, t6

**Material:**

Aluminum alloy 2024 or aluminum alloy 6061 or aluminum alloy 2024 or aluminum alloy 2024 or aluminum alloy 6061

**Surface Treatment:**

Black dye

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T252-d