

View Online at <https://aerobasegroup.com/nsn/5365-01-110-8141>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Casehardening Indicator:**

Not casehardened

**Chamfer Angle In Deg:**

45.0

**Chamfer Length:**

0.060 inches

**Width:**

0.380 inches

**Overall Length:**

Between 0.585 inches and 0.595 inches

**End Radius:**

0.120 inches

**Taper Minor Diameter:**

Between 5.000 inches and 5.005 inches

**Taper Major Diameter:**

5.130 inches

**Thread Size:**

5.875-16

**Depth:**

0.160 inches

**Bore Shape:**

Tapered

**Screw Thread Series Designator:**

Unj

**Drive Type:**

Slotted face

**Accommodation Type And Quantity:**

4 slots

**Angle Between Accommodations In Deg:**

90.0

**Beveled Thread:**

Not included

**Taper Major Diameter Location:**

Drive end

**Bore Annular Internal Serration:**

Not included

**Setscrew Locking Notch:**

Included

**Bore Edge Process:**

Chamfered and rounded

**Process End Location:**

Drive end and end opposite drive end

**Material:**

Aluminum alloy, qq-a-225/9, alloy 7075, t73 or aluminum alloy, ams 411, alloy 7049, t73 or ams 4108, alloy 7050, t73652 or ams 4050, alloy 7050, t73651

**Material:**

Aluminum alloy 7075 or aluminum alloy, ams 411, alloy 7049, t73 or ams 4108, alloy 7050, t73652 or ams 4050, alloy 7050, t73651

**Material Specification:**

Qq-a-225/9, alloy 7075, t73 federal specification 1st material response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T252-d