NSN 5365-01-115-2204

Shim - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5365-01-115-2204

Outside Diameter: Between 1.230 inches and 1.240 inches Aperture Diameter: Between 0.920 inches and 0.930 inches Construction: One-piece Material: Steel comp 301 or steel comp 302 or steel comp 303 or steel comp 316 or steel comp 321 Material Specification: Mil-s-5059 military specification 1st material response or mil-s-5059 military specification 2nd material response or specification 3rd material response or mil-s-5059 military specification 4th material response or ams 5510 assn stant response Style Designator:	_
Aperture Diameter: Between 0.920 inches and 0.930 inches Construction: One-piece Material: Steel comp 301 or steel comp 302 or steel comp 303 or steel comp 316 or steel comp 321 Material Specification: Mil-s-5059 military specification 1st material response or mil-s-5059 military specification 2nd material response or specification 3rd material response or mil-s-5059 military specification 4th material response or ams 5510 assn stant response	_
Between 0.920 inches and 0.930 inches Construction: One-piece Material: Steel comp 301 or steel comp 302 or steel comp 303 or steel comp 316 or steel comp 321 Material Specification: Mil-s-5059 military specification 1st material response or mil-s-5059 military specification 2nd material response or specification 3rd material response or mil-s-5059 military specification 4th material response or ams 5510 assn standards response	_
Construction: One-piece Material: Steel comp 301 or steel comp 302 or steel comp 303 or steel comp 316 or steel comp 321 Material Specification: Mil-s-5059 military specification 1st material response or mil-s-5059 military specification 2nd material response or specification 3rd material response or mil-s-5059 military specification 4th material response or ams 5510 assn stan response	_
One-piece Material: Steel comp 301 or steel comp 302 or steel comp 303 or steel comp 316 or steel comp 321 Material Specification: Mil-s-5059 military specification 1st material response or mil-s-5059 military specification 2nd material response or specification 3rd material response or mil-s-5059 military specification 4th material response or ams 5510 assn stantesponse	_
Material: Steel comp 301 or steel comp 302 or steel comp 303 or steel comp 316 or steel comp 321 Material Specification: Mil-s-5059 military specification 1st material response or mil-s-5059 military specification 2nd material response or specification 3rd material response or mil-s-5059 military specification 4th material response or ams 5510 assn stantesponse	_
Steel comp 301 or steel comp 302 or steel comp 303 or steel comp 316 or steel comp 321 Material Specification: Mil-s-5059 military specification 1st material response or mil-s-5059 military specification 2nd material response or specification 3rd material response or mil-s-5059 military specification 4th material response or ams 5510 assn stan response	_
Material Specification: Mil-s-5059 military specification 1st material response or mil-s-5059 military specification 2nd material response or specification 3rd material response or mil-s-5059 military specification 4th material response or ams 5510 assn stan response	_
Mil-s-5059 military specification 1st material response or mil-s-5059 military specification 2nd material response or specification 3rd material response or mil-s-5059 military specification 4th material response or ams 5510 assn stan response	_
specification 3rd material response or mil-s-5059 military specification 4th material response or ams 5510 assn stan response	_
response	ndard 5th material
Style Designator:	
otyle besignator.	
Circular	
Specification Data:	
70210-s8157 manufacturers standard	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A07000	
Mil-std (military Standard):	
Mil-s-5059 spec.	