NSN 5365-01-125-9230

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-01-125-9230

Thread Pitch Diameters:
+0.5188/+0.5194 inches
Thread Direction:
Right-hand
Casehardening Indicator:
Casehardened
Width:
0.470 inches
Overall Length:
0.960 inches
Taper Minor Diameter:
0.513 inches
Taper Major Diameter:
Between 0.523 inches and 0.524 inches
Thread Size:
5.250-12
Depth:
0.400 inches
Bore Shape:
Tapered
Screw Thread Series Designator:
Buttress
Drive Type:
Slotted face
Material Hardness Rating:
Between 25.0 rockwell c and 45.0 rockwell c
Accommodation Type And Quantity:
16 slots
Angle Between Accommodations In Deg:
45.0
Beveled Thread:
Not included
Taper Major Diameter Location:
Drive end
Bore Annular Internal Serration:
Not included
Setscrew Locking Notch:
Not included
Material:
Steel
Material:
Steel

NSN 5365-01-125-9230

Externally Threaded Ring - Page 2 of 2



$\overline{}$			-			
<u>ن</u>	irto	2	Iro	atn	าคท	

Phosphate

Surface Treatment:

Phosphate

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

Yes - demil/mli

Fiig:

T252-d