Externally Threaded Ring - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5365-01-128-4819



т	hread Class:
2	a
т	hread Direction:
R	light-hand
С	asehardening Indicator:
N	lot casehardened
W	Vidth:
В	etween 0.120 inches and 0.130 inches
0	overall Length:
0	.250 inches
т	hread Size:
3	.000-20
В	ore Diameter:
2	.650 inches
D	epth:
0	.030 inches
В	ore Shape:
S	traight
S	crew Thread Series Designator:
U	In
D	rive Type:
S	lotted inner face
т	hread Location:
В	oth ends
A	ccommodation Type And Quantity:
4	slots
A	ngle Between Accommodations In Deg:
9	0.0
В	eveled Thread:
Ir	ncluded
В	ore Annular Internal Serration:
N	lot included
S	etscrew Locking Notch:
Ν	lot included
N	laterial:
A	luminum alloy, qq-a-225/6, alloy 2024
N	laterial:
A	luminum alloy 2024
S	urface Treatment:
A	nodized
S	helf Life:
	l/a

NSN 5365-01-128-4819

Externally Threaded Ring - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

T252-d