NSN 5365-01-129-0934

Serrated Lock Ring - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5365-01-129-0934

Inside Diameter:
Between 0.387 inches and 0.394 inches
Pilot Diameter:
Between 0.486 inches and 0.501 inches
Overall Height:
Between 0.152 inches and 0.167 inches
Overall Outside Diameter:
Between 0.537 inches and 0.546 inches
Outer Serration Quantity:
14
Inner Serration Quantity:
24
Side Outer Serrations Omitted For Close Edge Installation:
Two sides
Material:
Steel, ams 5734
Material:
Steel, ams 5734
Steel, ams 5734 Surface Treatment:
Surface Treatment:
Surface Treatment: Passivate
Surface Treatment: Passivate Surface Treatment:
Surface Treatment: Passivate Surface Treatment: Passivated, qq-p-35
Surface Treatment: Passivate Surface Treatment: Passivated, qq-p-35 Shelf Life:
Surface Treatment: Passivate Surface Treatment: Passivated, qq-p-35 Shelf Life: N/a
Surface Treatment: Passivate Surface Treatment: Passivated, qq-p-35 Shelf Life: N/a Unit Of Measure:
Surface Treatment: Passivate Surface Treatment: Passivated, qq-p-35 Shelf Life: N/a Unit Of Measure:
Surface Treatment: Passivate Surface Treatment: Passivated, qq-p-35 Shelf Life: N/a Unit Of Measure: Demilitarization:
Surface Treatment: Passivate Surface Treatment: Passivated, qq-p-35 Shelf Life: N/a Unit Of Measure: Demilitarization: No
Surface Treatment: Passivate Surface Treatment: Passivated, qq-p-35 Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:
Surface Treatment: Passivate Surface Treatment: Passivated, qq-p-35 Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: