Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-01-129-4728

Thread Class: 2a Thread Direction: Right-hand Casehardened Width: 0.938 inches Overall Length: 0.938 inches Taper Major Diameter: 0.500 inches Thread Size: 0.500 inches Bore Diameter: 0.500 inches Bore Shape: Straight Scown Thread Series Designator: Uns Drive Type: Slotted inner face Accommodation Type And Quantity: 2 holes Angle Between Accommodations In Deg: 45.0 Beveled Thread: Not included
Thread Direction:Right-handCasehardening Indicator:Not casehardenedWidth:0.938 inchesOverall Length:0.938 inchesTaper Major Diameter:0.500 inchesThread Size:0.625-32Bore Diameter:0.500 inchesDepth:0.500 inchesSolo inchesDepth:0.500 inchesBore Shape:StraightStraightStraightSidted inner faceAccommodation Type And Quantity:2 holesAngle Between Accommodations In Deg:45.0Beveled Thread:
Right-handCasehardening Indicator:Not casehardenedWith:0.938 inchesOverall Length:0.938 inchesTaper Major Diameter:0.500 inchesThread Size:0.500 inchesBore Diameter:0.500 inchesDepth:0.500 inchesSolo inchesDepth:0.500 inchesDepth:0.500 inchesBore Shape:StraightScrew Thread Series Designator:UnsPive Type:Slotted inner faceAccommodation Type And Quantity:2 holesAngle Between Accommodations In Deg:45.0Beveled Thread:
Casehardening Indicator:Not casehardenedWidth:0.938 inchesOverall Length:0.938 inchesTaper Major Diameter:0.500 inchesThread Size:0.625-32Bore Diameter:0.500 inchesDepth:0.500 inchesSolo inchesDepth:0.500 inchesBore Shape:StraightScrew Thread Series Designator:UnsPive Type:Slotted inner faceAccommodation Type And Quantity:2 holesAngle Between Accommodations In Deg:45.0Beveled Thread:
Not casehardenedWidth:0.938 inchesOverall Length:0.938 inchesTaper Major Diameter:0.500 inchesThread Size:0.625-32Bore Diameter:0.500 inchesDepth:0.500 inchesBore Shape:StraightStraightStrow Thread Series Designator:UnsDive Type:Slotted inner faceAccommodation Type And Quantity:2 holesAngle Between Accommodations In Deg:45.0Beveled Thread:
Width:0.938 inchesOverall Length:0.938 inchesTaper Major Diameter:0.500 inchesThread Size:0.625-32Bore Diameter:0.500 inchesDepth:0.500 inchesBore Shape:StraightStraightDiver Type:Sloted inner faceAccommodation Type And Quantity:2 holesAngle Between Accommodations In Deg:45.0Beveled Thread:
0.938 inchesOverall Length:0.938 inchesTaper Major Diameter:0.500 inchesThread Size:0.625-32Bore Diameter:0.500 inchesDepth:0.500 inchesDepth:0.500 inchesBore Shape:StraightStraightDrive Type:Slotted inner faceAccommodation Type And Quantity:2 holesAngle Between Accommodations In Deg:45.0Beveled Thread:
Overall Length:0.938 inchesTaper Major Dianeter:0.500 inchesThread Size:0.625-32Bore Dianeter:0.500 inchesDepth:0.500 inchesBore Shape:StraightStraightDrive Type:Slotted inner faceAccommodation Type And Quantity:2 holesAngle Between Accommodations In Deg:6 sould in thread:6 sould in thread:7 sould in
0.938 inches Taper Major Diameter: 0.500 inches Thread Size: 0.625-32 Bore Diameter: 0.500 inches Depth: 0.500 inches Bore Shape: Straight Straight Strew Thread Series Designator: Uns Drive Type: Slotted inner face Accommodation Type And Quantity: 2 holes Magle Between Accommodations In Deg: 45.0
Taper Major Diameter:0.500 inchesThread Size:0.625-32Bore Diameter:0.500 inchesDepth:0.500 inchesBore Shape:StraightStraightDrive Type:Slotted inner faceAccommodation Type And Quantity:2 holesAngle Between Accommodations In Deg:45.0Beveled Thread:
 0.500 inches Thread Size: 0.625-32 Bore Diameter: 0.500 inches Depth: 0.500 inches Bore Shape: Straight Screw Thread Series Designator: Uns Drive Type: Slotted inner face Accommodation Type And Quantity: 2 holes Angle Between Accommodations In Deg: 45.0 Beveled Thread:
Thread Size:0.625-32Bore Diameter:0.500 inchesDepth:0.500 inchesBore Shape:0.500 inchesBore Shape:StraightScrew Thread Series Designator:UnsDrive Type:Slotted inner faceAccommodation Type And Quantity:2 holesAngle Between Accommodations In Deg:45.0Beveled Thread:
0.625-32Bore Diameter:0.500 inchesDepth:0.500 inchesBore Shape:StraightStrew Thread Series Designator:UnsDrive Type:Slotted inner faceAccommodation Type And Quantity:2 holesAngle Between Accommodations In Deg:45.0Beveled Thread:
Bore Diameter:0.500 inchesDepth:0.500 inchesBore Shape:StraightStraightCrew Thread Series Designator:UnsDrive Type:Slotted inner faceAccommodation Type And Quantity:2 holesAngle Between Accommodations In Deg:45.0Beveled Thread:
0.500 inchesDepth:0.500 inchesBore Shape:StraightScrew Thread Series Designator:UnsDrive Type:Slotted inner faceAccommodation Type And Quantity:2 holesAngle Between Accommodations In Deg:45.0Beveled Thread:
Depth:0.500 inchesBore Shape:StraightScrew Thread Series Designator:UnsDrive Type:Slotted inner faceAccommodation Type And Quantity:2 holesAngle Between Accommodations In Deg:45.0Beveled Thread:
0.500 inchesBore Shape:StraightScrew Thread Series Designator:UnsDrive Type:Slotted inner faceAccommodation Type And Quantity:2 holesAngle Between Accommodations In Deg:45.0Beveled Thread:
Bore Shape:StraightScrew Thread Series Designator:UnsDrive Type:Slotted inner faceAccommodation Type And Quantity:2 holesAngle Between Accommodations In Deg:45.0Beveled Thread:
StraightScrew Thread Series Designator:UnsDrive Type:Slotted inner faceAccommodation Type And Quantity:2 holesAngle Between Accommodations In Deg:45.0Beveled Thread:
Screw Thread Series Designator:UnsDrive Type:Slotted inner faceAccommodation Type And Quantity:2 holesAngle Between Accommodations In Deg:45.0Beveled Thread:
Uns Drive Type: Slotted inner face Accommodation Type And Quantity: 2 holes Angle Between Accommodations In Deg: 45.0 Beveled Thread:
Drive Type: Slotted inner face Accommodation Type And Quantity: 2 holes Angle Between Accommodations In Deg: 45.0 Beveled Thread:
Slotted inner face Accommodation Type And Quantity: 2 holes Angle Between Accommodations In Deg: 45.0 Beveled Thread:
Accommodation Type And Quantity: 2 holes Angle Between Accommodations In Deg: 45.0 Beveled Thread:
2 holes Angle Between Accommodations In Deg: 45.0 Beveled Thread:
Angle Between Accommodations In Deg: 45.0 Beveled Thread:
45.0 Beveled Thread:
Beveled Thread:
Not included
Taper Major Diameter Location:
Drive end
Bore Annular Internal Serration:
Not included
Setscrew Locking Notch:
Not included
Material:
Aluminum alloy, ww-t-785, t3-canceled
Material:
Aluminum alloy 2024
Shelf Life:
N/a

NSN 5365-01-129-4728

Externally Threaded Ring - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

T252-d