Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-01-130-4766

| Thread Class:  |
|--|
| 3a   |
| Thread Direction:  |
|  |
| Right-hand   |
| Casehardening Indicator:                                     |
| Not casehardened   |
| Overall Length:  |
| 0.225 inches   |
| Diameter:  |
| Between 0.250 inches and 0.256 inches                        |
| Thread Size:   |
| 2.125-16   |
| Bore Diameter:   |
| 1.250 inches   |
| Depth:   |
| 0.225 inches   |
| Bore Shape:  |
| Straight   |
| Screw Thread Series Designator:                              |
| Unj  |
| Drive Type:  |
| Drilled face   |
| Thread Location:   |
| Both ends  |
| Accommodation Type And Quantity:<br>6 holes                  |
|  |
| Angle Between Accommodations In Deg:<br>60.0                 |
| Radius From Geometric Axis To Accommodation:                 |
| 0.812 inches   |
| Beveled Thread:  |
| Included   |
| Bore Annular Internal Serration:                             |
| Not included   |
|  |
| Setscrew Locking Notch:<br>Not included                      |
| Material:  |
|  |
| Aluminum alloy, qq-a-200/11, alloy 7075, t73511<br>Material: |
|  |
| Aluminum alloy, qq-a-200/11, alloy 7075, t73511              |
| Shelf Life:  |
| N/a  |

## NSN 5365-01-130-4766

Externally Threaded Ring - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

T252-d