## NSN 5365-01-131-7887

Shim - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5365-01-131-7887

Outside Diameter: Between 0.744 inches and 0.747 inches  Aperture Diameter: Between 0.620 inches and 0.630 inches  Overall Thickness: 0.003 inches  Construction: One-piece  Material: Steel comp 301 or steel comp 302 or steel comp 303 or steel comp 316 or steel comp 321  Material Specification: Mil-s-5059 military specification 1st material response or mil-s-5059 military specification 2nd material response or mil-s-7 specification 3rd material response or mil-s-5059 military specification 4th material response or ams 5510 assn standard stresponse  Style Designator: Circular  Specification Data: 70210-s8157 manufacturers standard  Shelf Life:	
Aperture Diameter: Between 0.620 inches and 0.630 inches  Overall Thickness: 0.003 inches  Construction: One-piece  Material: Steel comp 301 or steel comp 302 or steel comp 303 or steel comp 316 or steel comp 321  Material Specification: Mil-s-5059 military specification 1st material response or mil-s-5059 military specification 2nd material response or mil-s-7 specification 3rd material response or mil-s-5059 military specification 4th material response or ams 5510 assn standard 5 response  Style Designator: Circular  Specification Data: 70210-s8157 manufacturers standard	
Between 0.620 inches and 0.630 inches  Overall Thickness: 0.003 inches  Construction: One-piece  Material: Steel comp 301 or steel comp 302 or steel comp 303 or steel comp 316 or steel comp 321  Material Specification: Mil-s-5059 military specification 1st material response or mil-s-5059 military specification 2nd material response or mil-s-7 specification 3rd material response or mil-s-5059 military specification 4th material response or ams 5510 assn standard 5 response  Style Designator: Circular  Specification Data: 70210-s8157 manufacturers standard	
Overall Thickness:  0.003 inches  Construction: One-piece  Material: Steel comp 301 or steel comp 302 or steel comp 303 or steel comp 316 or steel comp 321  Material Specification: Mil-s-5059 military specification 1st material response or mil-s-5059 military specification 2nd material response or mil-s-7 specification 3rd material response or mil-s-5059 military specification 4th material response or ams 5510 assn standard 5 response  Style Designator: Circular  Specification Data: 70210-s8157 manufacturers standard	
Construction: One-piece Material: Steel comp 301 or steel comp 302 or steel comp 303 or steel comp 316 or steel comp 321 Material Specification: Mil-s-5059 military specification 1st material response or mil-s-5059 military specification 2nd material response or mil-s-7 specification 3rd material response or mil-s-5059 military specification 4th material response or ams 5510 assn standard 5 response Style Designator: Circular Specification Data: 70210-s8157 manufacturers standard	
Construction: One-piece  Material: Steel comp 301 or steel comp 302 or steel comp 303 or steel comp 316 or steel comp 321  Material Specification: Mil-s-5059 military specification 1st material response or mil-s-5059 military specification 2nd material response or mil-s-7 specification 3rd material response or mil-s-5059 military specification 4th material response or ams 5510 assn standard 5 response  Style Designator: Circular  Specification Data: 70210-s8157 manufacturers standard	
One-piece  Material: Steel comp 301 or steel comp 302 or steel comp 303 or steel comp 316 or steel comp 321  Material Specification: Mil-s-5059 military specification 1st material response or mil-s-5059 military specification 2nd material response or mil-s-7 specification 3rd material response or mil-s-5059 military specification 4th material response or ams 5510 assn standard 5 response  Style Designator: Circular  Specification Data: 70210-s8157 manufacturers standard	
Material:  Steel comp 301 or steel comp 302 or steel comp 303 or steel comp 316 or steel comp 321  Material Specification:  Mil-s-5059 military specification 1st material response or mil-s-5059 military specification 2nd material response or mil-s-7 specification 3rd material response or mil-s-5059 military specification 4th material response or ams 5510 assn standard 5 response  Style Designator:  Circular  Specification Data:  70210-s8157 manufacturers standard	
Steel comp 301 or steel comp 302 or steel comp 303 or steel comp 316 or steel comp 321  Material Specification:  Mil-s-5059 military specification 1st material response or mil-s-5059 military specification 2nd material response or mil-s-7 specification 3rd material response or mil-s-5059 military specification 4th material response or ams 5510 assn standard 5 response  Style Designator:  Circular  Specification Data:  70210-s8157 manufacturers standard	
Material Specification:  Mil-s-5059 military specification 1st material response or mil-s-5059 military specification 2nd material response or mil-s-7059 military specification 4th material response or ams 5510 assn standard 5 response  Style Designator:  Circular  Specification Data:  70210-s8157 manufacturers standard	
Mil-s-5059 military specification 1st material response or mil-s-5059 military specification 2nd material response or mil-s-7 specification 3rd material response or mil-s-5059 military specification 4th material response or ams 5510 assn standard 5 response  Style Designator:  Circular  Specification Data:  70210-s8157 manufacturers standard	
specification 3rd material response or mil-s-5059 military specification 4th material response or ams 5510 assn standard 6 response  Style Designator:  Circular  Specification Data:  70210-s8157 manufacturers standard	
response  Style Designator: Circular  Specification Data: 70210-s8157 manufacturers standard	720 militar
Style Designator: Circular Specification Data: 70210-s8157 manufacturers standard	ith materia
Circular  Specification Data: 70210-s8157 manufacturers standard	
Specification Data: 70210-s8157 manufacturers standard	
70210-s8157 manufacturers standard	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A07000	
Mil-std (military Standard):	
Mil-s-5059 spec.	