

View Online at <https://aerobasegroup.com/nsn/5365-01-134-3124>

Thread Class:

3a

Thread Direction:

Right-hand

Casehardening Indicator:

Not casehardened

Overall Length:

Between 0.265 inches and 0.275 inches

Diameter:

Between 0.046 inches and 0.051 inches

Thread Size:

0.625-18

Bore Diameter:

Between 0.249 inches and 0.255 inches

Depth:

0.140 inches

Bore Shape:

Straight

Screw Thread Series Designator:

Unjf

Drive Type:

Drilled face

Thread Location:

End opposite drive end

Accommodation Type And Quantity:

3 holes

Angle Between Accommodations In Deg:

120.0

Radius From Geometric Axis To Accommodation:

0.235 inches

Beveled Thread:

Included

Bore Annular Internal Serration:

Not included

Setscrew Locking Notch:

Not included

Special Features:

Paint drilled face with two coats polyurethane enamel, mil-c-81773; color fed-std-595 no. 17875

Material:

Aluminum alloy, qq-a-200/3 or aluminum alloy, qq-a-225/6

Material:

Aluminum alloy 2024 or aluminum alloy 2024

Surface Treatment:

Anodized, p.S.13201, type 2, class b, fscm 82106

Surface Treatment:

Anodized, p.S.13201, type 2, class b, fscm 82106

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T252-d