## NSN 5365-01-138-4776

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-01-138-4776 **Thread Class:** 2a **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened **Chamfer Angle In Deg:** 60.0 Width: 0.250 inches **Overall Length:** Between 1.445 inches and 1.455 inches **Thread Size:** 3.250-12 **Bore Diameter:** 1.250 inches Depth: 0.812 inches **Bore Shape:** Straight **Screw Thread Series Designator:** Un **Drive Type:** Slotted face **Accommodation Type And Quantity:** 2 slots Angle Between Accommodations In Deg: 180.0 **Beveled Thread:** Not included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** Not included **Bore Edge Process:** Chamfered **Process End Location:** Drive end Material: Copper alloy, qq-c-465, comp 630 and aluminum bronze, qq-c-450, alloy 630 Material:

Copper alloy 630 and aluminum bronze, qq-c-450, alloy 630

## NSN 5365-01-138-4776

Externally Threaded Ring - Page 2 of 2



M	late	rial	Sp	ecif	icat	ion:
			~	••••		. •

Qq-c-465, comp 630 federal specification 1st material response

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

T252-d