

View Online at <https://aerobasegroup.com/nsn/5365-01-138-6639>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Casehardening Indicator:**

Not casehardened

**Chamfer Angle In Deg:**

60.0

**Width:**

0.250 inches

**Overall Length:**

Between 0.975 inches and 0.985 inches

**Thread Size:**

1.500-12

**Bore Diameter:**

0.562 inches

**Depth:**

0.375 inches

**Bore Shape:**

Straight

**Screw Thread Series Designator:**

Un

**Drive Type:**

Slotted face

**Accommodation Type And Quantity:**

2 slots

**Angle Between Accommodations In Deg:**

180.0

**Beveled Thread:**

Not included

**Bore Annular Internal Serration:**

Not included

**Setscrew Locking Notch:**

Not included

**Bore Edge Process:**

Chamfered

**Process End Location:**

Drive end

**Material:**

Copper alloy, qq-c-465, comp 630 and copper alloy, qq-c-450, comp 630

**Material:**

Copper alloy 630 and copper alloy, qq-c-450, comp 630

**Material Specification:**

Qq-c-465, comp 630 federal specification 1st material response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T252-d