## NSN 5365-01-144-1791



Externally Threaded Ring - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5365-01-144-1791 **Thread Class:** 2a **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened **Chamfer Angle In Deg:** 45.0 **Chamfer Length:** 0.050 inches Width: 0.125 inches **Overall Length:** 0.719 inches **Thread Size:** 1.062-12 **Bore Diameter:** 0.375 inches Depth: 0.125 inches Bore Shape: Straight **Screw Thread Series Designator:** Un **Drive Type:** Slotted face **Accommodation Type And Quantity:** Angle Between Accommodations In Deg: 180.0 **Beveled Thread:** Not included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** Not included **Bore Edge Process:** Chamfered **Process End Location:** End opposite drive end Material: Copper alloy, qq-c-465, comp 630 or copper alloy, qq-c-450, comp 630

## NSN 5365-01-144-1791

Externally Threaded Ring - Page 2 of 2



ate	

Copper alloy 630 or copper alloy, qq-c-450, comp 630

## **Material Specification:**

Qq-c-465, comp 630 federal specification 1st material response

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

T252-d