NSN 5365-01-148-3755

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-01-148-3755

| Thread Pitch Diameters: |
|--|
| +1.537/+1.541 inches |
| Thread Direction: |
| Right-hand |
| Casehardening Indicator: |
| Not casehardened |
| Overall Length: |
| Between 1.780 inches and 1.785 inches |
| Diameter: |
| Between 0.094 inches and 0.098 inches |
| Thread Size: |
| 1.562-32 |
| Bore Diameter: |
| Between 1.100 inches and 1.110 inches |
| Depth: |
| Between 0.058 inches and 0.060 inches |
| Bore Shape: |
| Straight |
| Screw Thread Series Designator: |
| Uns |
| Drive Type: |
| Drilled face |
| Accommodation Type And Quantity: |
| 2 holes |
| Angle Between Accommodations In Deg: |
| 180.0 |
| Radius From Geometric Axis To Accommodation: |
| 0.800 inches |
| Beveled Thread: |
| Not included |
| Bore Annular Internal Serration: |
| Not included |
| Setscrew Locking Notch: |
| Not included |
| Special Features: |
| Bored groove around circumference 1.415 in. Min dia, 1.420 in. Maximum dia |
| Material: |
| Aluminum alloy, qq-a-225/6, t4 |
| Material: |
| Aluminum alloy 2024 |
| Surface Treatment: |
| A = a -di= a |

Anodize

NSN 5365-01-148-3755

Externally Threaded Ring - Page 2 of 2



| _ | • | - | _ | | |
|------------|-------|---|-----|-----|------|
| C : | ırt 🔿 | 2 | ros | ıtm | ent: |
| | | | | | |

Anodized, mil-a-8625, type 2, class 2

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

T252-d