Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-01-156-6093

23 Thread Pitch Diameters: +0.973/+0.977 inches Thread Direction: Right-hand Casehardening Indicator: Not casehardened With: 0.060 inches Overall Length: Between 0.258 inches and 0.262 inches Thread Size: 1.000-32 Bore Diameter: 0.050 inches Dotto: Bore Diameter: 0.050 inches Bore Shape: Straight Straight Bore Manee Straight Straight Strated face Accommodation Type And Quantity: 4 slots Bore Annular Internal Serration: Not included Boter Annular Internal Serration: Not included Stater vecking Notch: Not included Stater state stype 303, cond a Material: States treatment:	Thread Class:	
Thread Pitch Diameters: +0.973/+0.977 inches Thread Direction: Right-hand Casehardening Indicator: Not casehardened Width: 0.000 inches Overall Length: Between 0.258 inches and 0.262 inches Thread Size: 1.000-32 Bore Diameter: 0.875 inches Depth: 0.875 inches Bore Shape: Straight Screw Thread Series Designator: Uns Drive Type: Slotted face Accommodation Type And Quantity: 4 slots Angle Between Accommodations In Deg: 0.00 Bored Thread: Not included Bore Annular Internal Serration: Not included Steel, astm a582 type 303, cond a Material: Steel, astm a582 type 303, cond a Material: Passivate		
+0.973/+0.977 inchesThread Direction:Right-handCasehardening Indicator:Not casehardenedWith:0.060 inchesOverall Length:Between 0.258 inches and 0.262 inchesThread Size:1.000-32Bore Diameter:0.875 inchesDepth:0.050 inchesBore Shape:StraightStraightStrew Thread Series Designator:UnsPrive Type:Slotted faceAccommodation Type And Quantity:4 slotsAngle Between Accommodations In Deg:90.0Bore Annular Internal Serration:Not includedBore Annular Internal Serration:Not includedMaterial:Stel, astm a582 type 303, cond aMaterial:PasivatePasivateSuitage Treatment:Pasivate		
Thread Direction: Right-hand Casehardening Indicator: Not casehardened Width: 0.060 inches Overall Length: Between 0.258 inches and 0.262 inches Thread Size: 1.000-32 Bore Diameter: 0.875 inches Depth: 0.050 inches Bore Shape: Straight Straight Straight Stotted face Accommodation Type And Quantity: 4 slots Angle Between Accommodations In Deg: 90.0 Bore Annular Internal Serration: Not included Bore Annular Internal Serration: Not included Stscrew Locking Notch: Not included Material: Stel, astm a582 type 303, cond a Material: Stel, astm a582 type 303, cond a Surface Treatment: Passwate		
Right-hand Casehardening Indicator: Not casehardened With: 0.060 inches Overall Length: Between 0.258 inches and 0.262 inches Thread Size: 1.000-32 Bore Diameter: 0.875 inches Depth: 0.650 inches Bore Shape: Straight Straight </td <td></td> <td></td>		
Casehardening Indicator: Not casehardened Width: 0.060 inches Overall Length: Between 0.258 inches and 0.262 inches Thread Size: 1.000-32 Bore Diameter: 0.875 inches Depth: 0.500 inches Bore Shape: Straight Screw Thread Series Designator: Uns Drive Type: Slotted face Accommodation Type And Quantity: 4 slots Breveed Thread: Not included Bore Annular Internal Serration: Not included Stater Stater Annular Internal Serration: Not included Stater Stater Annular Internal Serration: Not included Stater Stater ans 28 type 303, cond a Material: Steel, astm a582 type 303, cond a Surface Treatment: Passivate		
Not casehardened Width: 0.060 inches Overall Length: Between 0.258 inches and 0.262 inches Thread Size: 1.000-32 Bore Diameter: 0.875 inches Depth: 0.050 inches Bore Shape: Straight Screw Thread Series Designator: Uns Drive Type: Stotted face Accommodation Type And Quantity: 4 slots Angle Between Accommodations In Deg: 90.0 Beveled Thread: Not included Bore Annular Internal Serration: Not included Setscrew Locking Notch: Not included Material: Steel, astm a582 type 303, cond a Material: Passivate Surface Treatment: Passivate Surface		
Width:0.060 inchesOverall Length:Between 0.258 inches and 0.262 inchesThread Size:1.000-32Bore Diameter:0.875 inchesDepth:0.875 inchesBere Shape:StraightStrew Thread Series Designator:UnsDrive Type:Slotted faceAccommodation Type And Quantity:4 slotsAngle Between Accommodations In Deg:90.0Beveled Thread:Not includedBore Annular Internal Serration:Not includedStarserw Locking Notch:Not includedMaterial:Steel, astm a582 type 303, cond aMaterial:Steel, astm a582 type 303, cond a<		
Overall Length:Between 0.258 inches and 0.262 inchesThread Size:1.00-32Bore Diameter:0.875 inchesDepth:0.50 inchesBore Shape:StraightScrew Thread Series Designator:UnsDrive Type:Slotted faceAccommodation Type And Quantity:4 slotsAngle Between Accommodations In Deg:90.0Beveled Thread:Not includedBore Annular Internal Serration:Not includedSetscrew Locking Notch:Not includedMaterial:Steel, astm a582 type 303, cond aMaterial:Steel, astm a582 type 303, cond aSurface Treatment:PassivateSurface Treatment:PassivateSurface Treatment:Surface Treatment:	Width:	
Between 0.258 inches and 0.262 inches Thread Size: 1.000-32 Bore Diameter: 0.875 inches Depth: 0.050 inches Bore Shape: Straight Screw Thread Series Designator: Uns Drive Type: Slotted face Accommodation Type And Quantity: 4 slots Angle Between Accommodations In Deg: 90.0 Beveled Thread: Not included Bore Annular Internal Serration: Not included Setscrew Locking Notch: Not included Material: Steel, astm a582 type 303, cond a Material: Passivate Surface Treatment: Passivate	0.060 inches	
Between 0.258 inches and 0.262 inches Thread Size: 1.000-32 Bore Diameter: 0.875 inches Depth: 0.050 inches Bore Shape: Straight Screw Thread Series Designator: Uns Drive Type: Slotted face Accommodation Type And Quantity: 4 slots Angle Between Accommodations In Deg: 90.0 Beveled Thread: Not included Bore Annular Internal Serration: Not included Setscrew Locking Notch: Not included Material: Steel, astm a582 type 303, cond a Material: Passivate Surface Treatment: Passivate	Overall Length:	
1.000-32Bore Diameter:0.875 inchesDepth:0.050 inchesBore Shape:StraightScrew Thread Series Designator:UnsDrive Type:Slotted faceAccommodation Type And Quantity:4 slotsAngle Between Accommodations In Deg:90.0Beveled Thread:Not includedBore Annular Internal Serration:Not includedStescrew Locking Notch:Not includedSteel, astm a582 type 303, cond aMaterial:Steel, astm a582 type 303, cond aSurface Treatment:PasivateSurface Treatment:Not face Treatment:PasivateSurface Treatment:PasivateSurface Treatment:Surface Treatment:	Between 0.258 inches and 0.262 inches	
Bore Diameter: 0.875 inches Depth: 0.050 inches Bore Shape: Straight Screw Thread Series Designator: Uns Drive Type: Slotted face Accommodation Type And Quantity: 4 slots Angle Between Accommodations In Deg: 90.0 Beveled Thread: Not included Bore Annular Internal Serration: Not included Bore Annular Internal Serration: Not included Setscrew Locking Notch: Not included Material: Steel, astm a582 type 303, cond a Material: Steel, astm a582 type 303, cond a Surface Treatment: Passivate Surface Treatment:	Thread Size:	
0.875 inches Depth: 0.050 inches Bore Shape: Straight Screw Thread Series Designator: Uns Drive Type: Slotted face Accommodation Type And Quantity: 4 slots Angle Between Accommodations In Deg: 90.0 Beveled Thread: Not included Bore Annular Internal Serration: Not included Setscrew Locking Notch: Not included Setscrew Locking Notch: Not included Material: Steel, astm a582 type 303, cond a Material: Steel, astm a582 type 303, cond a Surface Treatment: Passivate Surface Treatment:	1.000-32	
Depth: 0.050 inches Bore Shape: Straight Screw Thread Series Designator: Uns Drive Type: Slotted face Accommodation Type And Quantity: 4 slots Angle Between Accommodations In Deg: 90.0 Beveled Thread: Not included Bore Annular Internal Serration: Not included Setscrew Locking Notch: Not included Material: Steel, astm a582 type 303, cond a Surface Treatment: Passivate Surface Treatment:	Bore Diameter:	
0.050 inches Bore Shape: Straight Screw Thread Series Designator: Uns Drive Type: Slotted face Accommodation Type And Quantity: 4 slots Angle Between Accommodations In Deg: 90.0 Beveled Thread: Not included Bore Annular Internal Serration: Not included Bore Annular Internal Serration: Not included Setscrew Locking Notch: Not included Setser Joseph Sologia Sologia Steel, astm a582 type 303, cond a Material: Steel, astm a582 type 303, cond a Surface Treatment: Passivate Surface Treatment:	0.875 inches	
0.050 inches Bore Shape: Straight Screw Thread Series Designator: Uns Drive Type: Slotted face Accommodation Type And Quantity: 4 slots Angle Between Accommodations In Deg: 90.0 Beveled Thread: Not included Bore Annular Internal Serration: Not included Setscrew Locking Notch: Not included Setscrew Locking Notch: Not included Steel, astm a582 type 303, cond a Material: Steel, astm a582 type 303, cond a Surface Treatment: Passivate	Depth:	
Straight Screw Thread Series Designator: Uns Drive Type: Slotted face Accommodation Type And Quantity: 4 slots Angle Between Accommodations In Deg: 90.0 Beveled Thread: Not included Bore Annular Internal Serration: Not included Setscrew Locking Notch: Not included Material: Steel, astm a582 type 303, cond a Material: Steel, astm a582 type 303, cond a Surface Treatment: Passivate Surface Treatment:	0.050 inches	
Screw Thread Series Designator: Uns Drive Type: Slotted face Accommodation Type And Quantity: 4 slots Angle Between Accommodations In Deg: 90.0 Beveled Thread: Not included Bore Annular Internal Serration: Not included Setscrew Locking Notch: Not included Material: Steel, astm a582 type 303, cond a Material: Steel, astm a582 type 303, cond a Surface Treatment: Passivate	Bore Shape:	
Uns Drive Type: Slotted face Accommodation Type And Quantity: 4 slots Angle Between Accommodations In Deg: 90.0 Beveled Thread: 90.0 Beveled Thread: Not included Bore Annular Internal Serration: Not included Setscrew Locking Notch: Not included Material: Steel, astm a582 type 303, cond a Material: Steel, astm a582 type 303, cond a Surface Treatment: Passivate Surface Treatment:	Straight	
Drive Type: Slotted face Accommodation Type And Quantity: 4 slots Angle Between Accommodations In Deg: 90.0 Beveled Thread: Not included Bore Annular Internal Serration: Not included Setscrew Locking Notch: Not included Material: Steel, astm a582 type 303, cond a Material: Steel, astm a582 type 303, cond a Surface Treatment: Passivate Surface Treatment:	Screw Thread Series Designator:	
Slotted face Accommodation Type And Quantity: 4 slots Angle Between Accommodations In Deg: 90.0 Beveled Thread: Not included Bore Annular Internal Serration: Not included Setscrew Locking Notch: Not included Material: Steel, astm a582 type 303, cond a Material: Steel, astm a582 type 303, cond a Surface Treatment: Passivate Surface Treatment:	Uns	
Accommodation Type And Quantity: 4 slots Angle Between Accommodations In Deg: 90.0 Beveled Thread: Not included Bore Annular Internal Serration: Not included Setscrew Locking Notch: Not included Material: Steel, astm a582 type 303, cond a Material: Steel, astm a582 type 303, cond a Surface Treatment: Passivate Passivate	Drive Type:	
4 slots Angle Between Accommodations In Deg: 90.0 Beveled Thread: Not included Bore Annular Internal Serration: Not included Setscrew Locking Notch: Not included Material: Steel, astm a582 type 303, cond a Material: Steel, astm a582 type 303, cond a Surface Treatment: Passivate Surface Treatment:	Slotted face	
Angle Between Accommodations In Deg:90.0Beveled Thread:Not includedBore Annular Internal Serration:Not includedSetscrew Locking Notch:Not includedMaterial:Steel, astm a582 type 303, cond aMaterial:Steel, astm a582 type 303, cond aSurface Treatment:PassivateSurface Treatment:	Accommodation Type And Quantity:	
90.0 Beveled Thread: Not included Bore Annular Internal Serration: Not included Setscrew Locking Notch: Not included Material: Steel, astm a582 type 303, cond a Material: Steel, astm a582 type 303, cond a Surface Treatment: Passivate Surface Treatment:	4 slots	
Beveled Thread: Not included Bore Annular Internal Serration: Not included Setscrew Locking Notch: Not included Material: Steel, astm a582 type 303, cond a Material: Steel, astm a582 type 303, cond a Surface Treatment: Passivate Surface Treatment:	Angle Between Accommodations In Deg:	
Not included Bore Annular Internal Serration: Not included Setscrew Locking Notch: Not included Material: Steel, astm a582 type 303, cond a Material: Steel, astm a582 type 303, cond a Surface Treatment: Passivate Surface Treatment:	90.0	
Bore Annular Internal Serration: Not included Setscrew Locking Notch: Not included Material: Steel, astm a582 type 303, cond a Material: Steel, astm a582 type 303, cond a Surface Treatment: Passivate Surface Treatment:	Beveled Thread:	
Not included Setscrew Locking Notch: Not included Material: Steel, astm a582 type 303, cond a Material: Steel, astm a582 type 303, cond a Surface Treatment: Passivate Surface Treatment:	Not included	
Setscrew Locking Notch: Not included Material: Steel, astm a582 type 303, cond a Material: Steel, astm a582 type 303, cond a Surface Treatment: Passivate Surface Treatment:	Bore Annular Internal Serration:	
Not included Material: Steel, astm a582 type 303, cond a Material: Steel, astm a582 type 303, cond a Surface Treatment: Passivate Surface Treatment:	Not included	
Material: Steel, astm a582 type 303, cond a Material: Steel, astm a582 type 303, cond a Surface Treatment: Passivate Surface Treatment:	Setscrew Locking Notch:	
Steel, astm a582 type 303, cond a Material: Steel, astm a582 type 303, cond a Surface Treatment: Passivate Surface Treatment:	Not included	
Material: Steel, astm a582 type 303, cond a Surface Treatment: Passivate Surface Treatment:	Material:	
Steel, astm a582 type 303, cond a Surface Treatment: Passivate Surface Treatment:	Steel, astm a582 type 303, cond a	
Surface Treatment: Passivate Surface Treatment:	Material:	
Passivate Surface Treatment:	Steel, astm a582 type 303, cond a	
Surface Treatment:	Surface Treatment:	
	Passivate	
Passivated an p 35	Surface Treatment:	
rassivaleu, yy-p-ss	Passivated, qq-p-35	

NSN 5365-01-156-6093

Externally Threaded Ring - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T252-d

