NSN 5365-01-160-2422

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-01-160-2422 **Thread Class:** 2a **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened **Chamfer Angle In Deg:** 60.0 Width: 0.250 inches **Overall Length:** Between 1.021 inches and 1.031 inches **Thread Size:** 1.375-12 **Bore Diameter:** 0.375 inches Depth: Between 0.618 inches and 0.622 inches **Bore Shape:** Straight **Screw Thread Series Designator:** Unf **Drive Type:** Slotted face **Accommodation Type And Quantity:** 2 slots Angle Between Accommodations In Deg: 180.0 **Beveled Thread:** Not included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** Included **Bore Edge Process:** Chamfered **Process End Location:** Drive end Material: Copper alloy, qq-c-450 or copper alloy, qq-c-465

Material:

Copper alloy, qq-c-450 or copper alloy, qq-c-465

NSN 5365-01-160-2422

Externally Threaded Ring - Page 2 of 2



_				-		
C	h	0	Iŧ.		ife:	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T252-d