Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-01-163-6135

т	hread Class:
3	a
т	hread Direction:
R	ight-hand
С	asehardening Indicator:
Ν	ot casehardened
V	/idth:
0	040 inches
С	verall Length:
0	188 inches
т	hread Size:
3	250-32
В	ore Diameter:
3	000 inches
D	epth:
0	060 inches
В	ore Shape:
S	traight
S	crew Thread Series Designator:
U	ns
D	rive Type:
S	lotted face
Т	hread Location:
В	oth ends
A	ccommodation Type And Quantity:
2	slots
A	ngle Between Accommodations In Deg:
1	80.0
B	eveled Thread:
lr	cluded
B	ore Annular Internal Serration:
Ν	ot included
S	etscrew Locking Notch:
	ot included
B	ore Edge Process:
A	ny acceptable
S	pecial Features:
	yed black
	laterial:
	luminum alloy, qq-a-200/11, alloy 7075, t6511
N	laterial:
Α	luminum alloy, qq-a-200/11, alloy 7075, t6511

NSN 5365-01-163-6135

Externally Threaded Ring - Page 2 of 2



Surface Treatment:

Anodized, ps13201, type 2, cl 2 fscm 76301

Surface Treatment:

Anodized, ps13201, type 2, cl 2 fscm 76301

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T252-d