

View Online at <https://aerobasegroup.com/nsn/5365-01-172-3725>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Casehardening Indicator:**

Not casehardened

**Width:**

0.315 inches

**Overall Length:**

Between 0.940 inches and 0.950 inches

**Thread Size:**

3.625-16

**Bore Diameter:**

Between 2.900 inches and 2.905 inches

**Depth:**

Between 0.300 inches and 0.310 inches

**Bore Shape:**

Straight

**Screw Thread Series Designator:**

Un

**Drive Type:**

Slotted face

**Accommodation Type And Quantity:**

4 slots

**Angle Between Accommodations In Deg:**

90.0

**Beveled Thread:**

Not included

**Bore Annular Internal Serration:**

Not included

**Setscrew Locking Notch:**

Not included

**Special Features:**

Cbore on drive end 0.630 in. Deep by 3.225 in. Diameter, cbore opposite drive end 0.240 in. Min and 0.250 in. Maximum deep by 3.096 in. Min and 3.098 maximum diameter, color white, fed standard 595, no. 17875; thd end anodized

**Material:**

Aluminum alloy, qq-a-225/9, alloy 7075, t7351

**Material:**

Aluminum alloy 7075

**Surface Treatment:**

Enamel, mms-420, ps13630, fscm 76301

**Surface Treatment:**

Enamel, mms-420, ps13630, fscm 76301

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T252-d