

View Online at <https://aerobasegroup.com/nsn/5365-01-172-3725>

Thread Class:

3a

Thread Direction:

Right-hand

Casehardening Indicator:

Not casehardened

Width:

0.315 inches

Overall Length:

Between 0.940 inches and 0.950 inches

Thread Size:

3.625-16

Bore Diameter:

Between 2.900 inches and 2.905 inches

Depth:

Between 0.300 inches and 0.310 inches

Bore Shape:

Straight

Screw Thread Series Designator:

Un

Drive Type:

Slotted face

Accommodation Type And Quantity:

4 slots

Angle Between Accommodations In Deg:

90.0

Beveled Thread:

Not included

Bore Annular Internal Serration:

Not included

Setscrew Locking Notch:

Not included

Special Features:

Cbore on drive end 0.630 in. Deep by 3.225 in. Diameter, cbore opposite drive end 0.240 in. Min and 0.250 in. Maximum deep by 3.096 in. Min and 3.098 maximum diameter, color white, fed standard 595, no. 17875; thd end anodized

Material:

Aluminum alloy, qq-a-225/9, alloy 7075, t7351

Material:

Aluminum alloy 7075

Surface Treatment:

Enamel, mms-420, ps13630, fscm 76301

Surface Treatment:

Enamel, mms-420, ps13630, fscm 76301

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T252-d