## NSN 5365-01-172-7863

Passivate

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-01-172-7863

Thread Pitch Diameters:
+0.898/+0.936 inches
Thread Direction:
Right-hand
Casehardening Indicator:
Not casehardened
Width:
0.060 inches
Overall Length:
0.500 inches
Thread Size:
0.938-32
Bore Diameter:
0.060 inches
Depth:
0.060 inches
Bore Shape:
Straight
Screw Thread Series Designator:
Nonstandard
Drive Type:
Slotted face
Thread Location:
Drive end
Accommodation Type And Quantity:
2 slots
Angle Between Accommodations In Deg:
180.0
Beveled Thread:
Not included
Bore Annular Internal Serration:
Not included
Setscrew Locking Notch:
Not included
Special Features:
Drive end counterbore 0.563 diameter x0.094 deep and second end counterbore 0.781 diameter x 0.343 deep 63aa finish
Material:
Steel, qq-s-763, class 303, cond a
Material:
Steel comp 303
Surface Treatment:

## NSN 5365-01-172-7863

Externally Threaded Ring - Page 2 of 2



	tment	

Passivated, mil-std-171, finish 5.4.1

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

T252-d