

View Online at <https://aerobasegroup.com/nsn/5365-01-174-8873>

Thread Class:

2a

Thread Direction:

Right-hand

Casehardening Indicator:

Not casehardened

Overall Length:

0.438 inches

Diameter:

0.129 inches

Thread Size:

3.000-16

Bore Diameter:

1.375 inches

Depth:

0.250 inches

Bore Shape:

Straight

Screw Thread Series Designator:

Un

Drive Type:

Drilled face

Accommodation Type And Quantity:

3 holes

Angle Between Accommodations In Deg:

90.0 and 180.0

Radius From Geometric Axis To Accommodation:

1.188 inches

Beveled Thread:

Not included

Bore Annular Internal Serration:

Not included

Setscrew Locking Notch:

Not included

Special Features:

Chole opposite drive end 2.125 in. Diameter by 0.1905 in. Min and 0.1925 in. Maximum deep

Material:

Steel, qq-s-763, cond a

Material:

Steel comp 202 or steel comp 302 or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 309 or steel comp 310 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 322 or steel comp 324 or steel comp 347 or steel comp 633 or steel comp 634 or steel comp 403 or steel comp 405 or steel comp 410 or steel comp 414 or steel comp 416 or steel comp 416se or steel comp 420 or steel comp 430 or steel comp 430f or steel comp 430fse or steel comp 431 or steel comp 440a or steel comp 440b or steel comp 440c or steel comp 440f or steel comp 440fse or steel comp 446

Shelf Life:

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T252-d