NSN 5365-01-183-1669

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-01-183-1669

| view Online at https://aerobasegroup.com/nsn/5 |
|--|
| Thread Pitch Diameters: |
| +1.102/+1.105 inches |
| Thread Direction: |
| Right-hand |
| Casehardening Indicator: |
| Not casehardened |
| Width: |
| Between 0.060 inches and 0.070 inches |
| Overall Length: |
| Between 0.170 inches and 0.175 inches |
| Thread Size: |
| 1.118-56 |
| Bore Diameter: |
| Between 0.978 inches and 0.980 inches |
| Depth: |
| Between 0.040 inches and 0.050 inches |
| Bore Shape: |
| Straight |
| Screw Thread Series Designator: |
| Uns |
| Drive Type: |
| Slotted face |
| Accommodation Type And Quantity: |
| 4 slots |
| Angle Between Accommodations In Deg: |
| 45.0 |
| Beveled Thread: |
| Not included |
| Bore Annular Internal Serration: |
| Not included |
| Setscrew Locking Notch: |
| Not included |
| Material: |
| Steel, astm a582, type 416, cond a |
| Material: |
| Steel, astm a582, type 416, cond a |
| Surface Treatment: |
| Passivate |
| Surface Treatment: |
| Passivated, qq-p-35 |
| Shelf Life: |
| N/a |
| |

NSN 5365-01-183-1669

Externally Threaded Ring - Page 2 of 2



| | • • | | | | |
|----|-----|-------------|----|-----|------|
| In | 18 | <i>(</i>)+ | МА | 261 | ıre: |
| | | | | | |

--

Demilitarization:

No

Fiig:

T252-d