## NSN 5365-01-186-7227

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-01-186-7227 **Thread Class:** 2a **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened **Chamfer Angle In Deg:** 45.0 **Chamfer Length:** 0.062 inches **Overall Length:** Between 0.984 inches and 1.000 inches Diameter: 0.406 inches **Thread Size:** 6.000-12 **Bore Diameter:** 3.750 inches Depth: 0.363 inches Bore Shape: Straight **Screw Thread Series Designator:** Un **Drive Type:** Drilled face **Accommodation Type And Quantity:** Angle Between Accommodations In Deg: 60.0 **Radius From Geometric Axis To Accommodation:** 2.500 inches **Beveled Thread:** Not included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** Not included **Bore Edge Process:** Chamfered

**Process End Location:** 

Both ends

## NSN 5365-01-186-7227

Externally Threaded Ring - Page 2 of 2



NЛ	2	te	r	2	

Copper alloy, qq-c-465, comp 630 or copper alloy qq-c-465, comp 606 or 614 or 642

Material:

Copper alloy 630 or copper alloy qq-c-465, comp 606 or 614 or 642

**Material Specification:** 

Qq-c-465, comp 630 federal specification 1st material response

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_\_

Demilitarization:

No

Fiig:

T252-d