NSN 5365-01-194-8562

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-01-194-8562 **Thread Class:** За **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened **Chamfer Angle In Deg:** 45.0 **Chamfer Length:** 0.029 inches **Overall Length:** Between 0.561 inches and 0.565 inches Diameter: 0.250 inches **End Radius:** 0.718 inches **Thread Size:** 2.250-12 **Bore Diameter:** Between 1.380 inches and 1.385 inches Depth: 0.350 inches **Bore Shape:** Straight **Screw Thread Series Designator:** British standard buttress **Drive Type:** Drilled face **Thread Location:** Both ends **Accommodation Type And Quantity:**

Angle Between Accommodations In Deg: 90.0 **Radius From Geometric Axis To Accommodation:** 0.875 inches **Beveled Thread:** Included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** Not included

NSN 5365-01-194-8562

Externally Threaded Ring - Page 2 of 2



Bore Edge Process:
Chamfered
Process End Location:
Both ends
Special Features:
8 holes, 0.070 in. Dia, equally spaced, drilled at a 45 degrees angle, from the face through the periphery
Material:
Steel, st0160lb0012, alloy 9-4-30, fscm 43999
Material:
Steel, st0160lb0012, alloy 9-4-30, fscm 43999
Surface Treatment:
Nickel
Surface Treatment:
Nickel plated
Shelf Life:
N/a
Unit Of Measure:
- -
Demilitarization:
No
Fiig:
T252-d