

View Online at <https://aerobasegroup.com/nsn/5365-01-195-6221>

**Thread Direction:**

Right-hand

**Countersink Angle In Deg:**

30.0 and 30.0

**Overall Length:**

2.000 inches

**Diameter:**

2.000 inches

**Thickness:**

0.500 inches

**Wrenching Facility Shape:**

Flat

**Countersink Depth:**

Between 0.020 inches and 0.050 inches and 0.340 inches and 0.380 inches

**Screw Thread Length:**

1.375 inches

**Width Across Flats:**

1.880 inches

**Countersink Location:**

Threaded end and wrenching end

**Hole Inside Diameter:**

Between 1.2495 inches and 1.2505 inches

**Features Provided:**

Countersunk

**Thready Qty Per Inch (tpi):**

8

**Thread Size:**

1.750 inches

**Material:**

Steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 or steel comp 1023 or steel comp 1025 or steel comp 1026 or steel comp 1117 or steel comp 1119

**Material Specification:**

Astm a108 assn standard 1st material response or astm a576 assn standard 2nd material response or astm a519 assn standard 3rd material response

**Surface Treatment:**

Phosphate manganese

**Surface Treatment Specification:**

Dod-p-16232, type m, class 2 military specification single treatment response

**Thread Series Designator:**

Un

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A540s0

**Mil-std (military Standard):**

spec.