NSN 5365-01-205-3882



Machine Thread Bushing - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5365-01-205-3882 **Thread Direction:** Right-hand **Countersink Angle In Deg:** 60.0 and 60.0 Slot Depth: Between 0.142 inches and 0.165 inches Slot Width: Between 0.170 inches and 0.190 inches **Overall Length:** Between 0.667 inches and 0.676 inches Wrenching Facility Shape: Slotted **Screw Thread Length:** Between 0.419 inches and 0.444 inches **Countersink Location:** Threaded end and wrenching end **Hole Inside Diameter:** Between 1.400 inches and 1.420 inches **Features Provided:** Countersunk Thready Qty Per Inch (tpi): 20 **Thread Size:** 1.875 inches **Special Features:** Four bolt holes 0.153 in. Min and 0.162 in. Maximum diameter equally spaced on a 2.000 in. Diameter bolt circle; four slots 0.110 in. Min and 0.130 in. Maximum wide and 0.045 in. Min and 0.065 in. Maximum deep equally spaced on threaded end Material: Steel comp e4340 or steel comp 4340 **Material Specification:** Mil-s-5000 military specification 1st material response or ams 6415 assn standard 2nd material response **Thread Series Designator:** Un Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

Mil-std (military Standard): Mil-s-5000 spec.

Fiig: A540s0