

View Online at <https://aerobasegroup.com/nsn/5365-01-205-3882>

**Thread Direction:**

Right-hand

**Countersink Angle In Deg:**

60.0 and 60.0

**Slot Depth:**

Between 0.142 inches and 0.165 inches

**Slot Width:**

Between 0.170 inches and 0.190 inches

**Overall Length:**

Between 0.667 inches and 0.676 inches

**Wrenching Facility Shape:**

Slotted

**Screw Thread Length:**

Between 0.419 inches and 0.444 inches

**Countersink Location:**

Threaded end and wrenching end

**Hole Inside Diameter:**

Between 1.400 inches and 1.420 inches

**Features Provided:**

Countersunk

**Thready Qty Per Inch (tpi):**

20

**Thread Size:**

1.875 inches

**Special Features:**

Four bolt holes 0.153 in. Min and 0.162 in. Maximum diameter equally spaced on a 2.000 in. Diameter bolt circle; four slots 0.110 in. Min and 0.130 in. Maximum wide and 0.045 in. Min and 0.065 in. Maximum deep equally spaced on threaded end

**Material:**

Steel comp e4340 or steel comp 4340

**Material Specification:**

Mil-s-5000 military specification 1st material response or ams 6415 assn standard 2nd material response

**Thread Series Designator:**

Un

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A540s0

**Mil-std (military Standard):**

Mil-s-5000 spec.