

View Online at <https://aerobasegroup.com/nsn/5365-01-211-0832>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Casehardening Indicator:**

Not casehardened

**Width:**

0.250 inches

**Overall Length:**

0.750 inches

**Thread Size:**

2.000-16

**Bore Diameter:**

Between 0.813 inches and 0.814 inches

**Depth:**

0.188 inches

**Bore Shape:**

Straight

**Screw Thread Series Designator:**

Un

**Drive Type:**

Slotted face

**Material Hardness Rating:**

Not rated

**Thread Location:**

Both ends

**Accommodation Type And Quantity:**

2 slots

**Angle Between Accommodations In Deg:**

180.0

**Beveled Thread:**

Included

**Bore Annular Internal Serration:**

Not included

**Setscrew Locking Notch:**

Not included

**Special Features:**

Pilot on end opposite wrenching facili type 1.188 in. Diameter and 0.346 in. Min and 0.349 in. Maximum lg

**Material:**

Copper alloy, qq-c-390

**Material:**

Copper alloy 820 or copper alloy 824 or copper alloy 825 or copper alloy 826 or copper alloy 827 or copper alloy 828 or copper alloy 836 or copper alloy 838 or copper alloy 842 or copper alloy 844 or copper alloy 848 or copper alloy 852 or copper alloy 854 or copper alloy 855 or copper alloy 857 or copper alloy 861 or copper alloy 862 or copper alloy 863 or copper alloy 864 or copper alloy 865 or copper alloy 868 or copper alloy 872 or copper alloy 874 or copper alloy 903 or copper alloy 905 or copper alloy 907 or copper alloy 910 or copper alloy 913 or

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T252-d