## NSN 5365-01-213-7852

Machine Thread Bushing - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-01-213-7852

view Offilite at https://aerobasegroup.com/histr/0000-01-210-7002
Thread Direction:
Right-hand
Countersink Angle In Deg:
45.0
Slot Depth:
Between 0.120 inches and 0.170 inches
Slot Width:
Between 0.230 inches and 0.250 inches
Overall Length:
Between 1.030 inches and 1.060 inches
Thickness:
Between 0.150 inches and 0.160 inches
Wrenching Facility Shape:
Slotted
Countersink Depth:
Between 0.040 inches and 0.060 inches
Screw Thread Length:
Between 0.350 inches and 0.390 inches
Countersink Location:
Wrenching end
Hole Inside Diameter:
Between 0.850 inches and 0.870 inches
Features Provided:
Countersunk
Thready Qty Per Inch (tpi):
18
Thread Size:
1.3125 inches
Special Features:
Polymide insert ring above threads; quench and temper to rockwell c 26.0 min and 32.0 max
Material:
Steel
Material Specification:
Ams 6371 assn standard single material response or ams 6370 assn standard single material response
Surface Treatment:
Oxide
Surface Treatment Specification:
Mil-c-13924 military specification single treatment response
Thread Series Designator:
Unjef
Shelf Life:
N/a

## NSN 5365-01-213-7852

Machine Thread Bushing - Page 2 of 2



Ini	1 (	Of	ΝЛ	മാ	e i	ırc	٠.

--

Demilitarization:

No

Fiig:

A540s0

Mil-std (military Standard):

Mil-c-13924 spec.