NSN 5365-01-215-2842

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-01-215-2842 **Thread Class:** За **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened Chamfer Angle In Deg: 45.0 **Chamfer Length:** Between 0.020 inches and 0.040 inches Width: Between 0.230 inches and 0.250 inches **Overall Length:** Between 0.530 inches and 0.560 inches **Thread Size:** 2.750-16 **Bore Diameter:** Between 2.290 inches and 2.310 inches Depth: 0.080 inches **Bore Shape:** Straight **Screw Thread Series Designator:** Unj **Drive Type:** Slotted bore **Material Hardness Rating:** Between 26.0 rockwell c and 32.0 rockwell c **Thread Location:** Both ends **Accommodation Type And Quantity:** Angle Between Accommodations In Deg: 60.0 **Beveled Thread:** Included **Bore Annular Internal Serration: Setscrew Locking Notch:**

Not included

Setscrew Locking Not included

Bore Edge Process:

Chamfered

NSN 5365-01-215-2842

Externally Threaded Ring - Page 2 of 2



Process End Location: Both ends **Special Features:** Color black; polyimide insert ring on drive end Material: Steel, ams 6371 or steel, ams 6370 Material: Steel comp 4130 or steel, ams 6370 **Surface Treatment:** Oxide, mil-c-13924 **Surface Treatment:** Oxide, mil-c-13924 Shelf Life: N/a **Unit Of Measure:** Demilitarization:

No **Fiig:** T252-d