NSN 5365-01-217-3082



Machine Thread Bushing - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5365-01-217-3082 **Thread Direction:** Right-hand **Countersink Angle In Deg:** 90.0 Slot Depth: 0.084 inches **Slot Width:** 0.062 inches **Overall Length:** 0.312 inches **Wrenching Facility Shape:** Slotted **Countersink Depth:** Between 0.010 inches and 0.030 inches **Screw Thread Length:** 0.170 inches **Countersink Location:** Wrenching end **Hole Inside Diameter:** Between 0.132 inches and 0.136 inches **Features Provided:** Countersunk Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.250 inches Material: Steel or steel comp 303se or steel comp 416 or steel comp 302 or steel comp 303 or steel comp 304 or steel comp 304l or steel comp 316 or steel comp 347 or steel comp 410 **Material Specification:** Ams 5640 assn standard single material response or astm a582 assn standard single material response or astm a582, type 303se assn standard single material response or qq-s-763, type 416, 302, 303, 304, 304l, 316 cond a, 347 or 410 federal specification single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a

NI-

Unit Of Measure:

Demilitarization:

NSN 5365-01-217-3082

Machine Thread Bushing - Page 2 of 2



Fiig:

A540s0