NSN 5365-01-218-7729

Externally Threaded Ring - Page 1 of 2



Externally Tricaded King Tage 1 of 2
View Online at https://aerobasegroup.com/nsn/5365-01-218-7729
Thread Pitch Diameters:
+3.1005/+3.1037 inches
Thread Direction:
Right-hand
Casehardening Indicator:
Not casehardened
Overall Length:
Between 0.100 inches and 0.110 inches
Diameter:
0.136 inches
Thread Size:
3.125-32
Bore Diameter:
2.625 inches
Depth:
Between 0.100 inches and 0.110 inches
Bore Shape:
Straight
Screw Thread Series Designator:
Nonstandard
Drive Type:
Drilled face
Accommodation Type And Quantity:
4 holes
Angle Between Accommodations In Deg:
90.0
Radius From Geometric Axis To Accommodation:
1.406 inches
Beveled Thread:
Not included
Bore Annular Internal Serration:
Not included
Setscrew Locking Notch:
Not included
Bore Edge Process:
Any acceptable

Material:

Steel, astm a582, type 303

Material:

Steel comp 303

Surface Treatment:

Passivate

NSN 5365-01-218-7729

Externally Threaded Ring - Page 2 of 2



	Trea	

Passivated, qq-p-35

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T252-d